



## Gator-Laid® Wire Rope Slings with Parallel Eyes

US Patent #5,561,973

For heavy lifting work this is the most efficient wire rope sling that meets all industrial and regulatory standards. This sling and the Gator-Max® sling are identical except the Gator-Laid® sling has metal sleeves for the splice connection. This is the product when a big lift but shorter sling is required. It has twelve parts of wire rope in the loop. The Gator-Laid® products were developed in conjunction with the offshore oil industry to provide the world's best heavy lift wire rope slings. This sling has great flexibility.



### GATOR-LAID® SLINGS TECHNICAL CHART

Finished Diameter	Component Parts	Standard Eye Size	Vertical Rated Capacity (tons)	Choker Rated Capacity (tons)	Basket Rated Capacity (tons)	Weight Per Foot (lbs.)
1/2"	1/8"	8"	1.4	1.0	2.8	.26
5/8"	5/32"	10"	2.0	1.5	4.0	.40
3/4"	3/16"	12"	3.0	2.2	6.0	.59
7/8"	7/32"	14"	4.0	3.0	8.0	.77
1"	1/4"	16"	4.8	3.6	9.6	.99
1-1/4"	5/16"	18"	7.5	5.6	15.0	1.56
1-1/2"	3/8"	20"	10.5	7.8	21.0	2.19
1-3/4"	7/16"	22"	14.6	10.9	29.2	3.15
2"	1/2"	24"	19.1	14.3	38.2	4.14
2-1/4"	9/16"	26"	24.1	18.0	48.2	5.31
2-1/2"	5/8"	28"	29.6	22.2	59.2	6.48
3"	3/4"	30"	42.3	31.7	84.6	9.36
3-1/2"	7/8"	35"	57.3	42.9	114.6	12.78
4"	1"	40"	74.4	55.8	148.4	16.65
4-1/2"	1-1/8"	45"	93.6	60.2	187.2	21.06
5"	1-1/4"	50"	115.0	86.2	230.0	26.01
5-1/2"	1-3/8"	55"	138.2	103.6	276.4	31.50
6"	1-1/2"	60"	164.1	123.0	328.2	37.44
7"	1-3/4"	70"	220.3	165.2	440.6	51.03
8"	2"	80"	285.1	213.8	570.2	66.51
9"	2-1/4"	90"	355.6	266.7	711.2	84.24
10"	2-1/2"	100"	434.8	326.1	869.6	104.00

**NOTE:** Rated capacity is based on 5:1 Design Factor.

## **⚠ WARNING**

Inspect before use. Follow OSHA, ANSI B30.9 and Manufacturer's Guidelines. Use by untrained persons is hazardous. Improper use will result in serious injury or death. Do not exceed rate capacity. This product will fail if damaged, abused, misused, overused or improperly maintained.