



Twin-Path® Two-Leg Bridles

TL Simply the lightest and strongest synthetic bridles in the world today. These are perfect to replace existing chain and wire rope bridles. The Twin-Path® synthetic bridle with K-Spec® core yarn is less than half the weight of any steel assembly. The soft eye at the top goes on the crane hook and there is no heavy steel ring to deal with. If you need a four-leg bridle, order two Twin-Path® Two-Leg Bridles.

TWIN-PATH® TWO-LEG BRIDLES (Capacities in lbs.)

Stock Numbers	Vertical	60° Horizontal Angle (Lbs.)	Wt. Per Ft.	Nominal Width
TPXCTL 1,000	10,000	8,500	.34	3"
TPXCTL 1,500	15,000	12,750	.44	3"
TPXCTL 2,000	20,000	17,000	.61	3"
TPXCTL 3,000	30,000	25,500	.88	4"
TPXCTL 4,000	40,000	34,000	1.23	5"
TPXCTL 5,000	50,000	42,500	1.65	5"



Twin-Path® Eye & Eye Synthetic Sling

EE Riggers have told us that they have some applications where they want an eye and eye sling only and this is the one with all of the Twin-Path® features in a strictly eye and eye product. It is a single-bodied sling with integrated eyes.

TWIN-PATH® EYE & EYE SLING (Capacities in lbs.)

Stock Numbers	Vertical	Choker	Vertical Basket	Basket 60°	Wt Lbs. Per Ft.	Nominal Width
TPXCEE 1,000	10,000	8,000	20,000	17,320	.28	3"
TPXCEE 1,500	15,000	12,000	30,000	25,980	.36	3"
TPXCEE 2,000	20,000	16,000	40,000	36,640	.50	3"
TPXCEE 2,500	25,000	20,000	50,000	43,300	.60	4"
TPXCEE 3,000	30,000	24,000	60,000	51,960	.75	4"
TPXCEE 4,000	40,000	32,000	80,000	69,280	1.00	5"
TPXCEE 5,000	50,000	40,000	100,000	86,139	1.40	5"

METRIC CAPACITIES AVAILABLE

! WARNING

Sling can fail if damaged, misused or overloaded. Inspect before use. Damaged sling shall not be used. Use only if trained. Do not exceed rated capacity. Protect sling from being cut by load edges, corners, protrusions and abrasive surfaces. Avoid exposure to acid, alkali and temperature over 180°F. DEATH or INJURY can occur from improper use or maintenance.