

Hardware Type Webbing Slings Steel

WITH ALLOY STEEL END FITTINGS

The inclusion of alloy steel end fittings to nylon webbing increases sling life substantially.


WSA TYPE I BASKET SLING TRIANGLES BOTH ENDS



WIDTH INCHES	NUMBER PLIES	RATED CAPACITY (LBS)			CODE NUMBER
		CHOKER	VERTICAL	BASKET	
2	1		2400	4800	6I-STT
2	2		4800	9600	6DI-STT
2	1		3200	6400	9I-STT
2	2		6200	12400	9DI-STT
3	1		3600	7200	6M-STT
3	2		6660	13320	6DM-STT
3	1		4800	9600	9M-STT
3	2		8880	17760	9DM-STT
4	1		4800	9600	6P-STT
4	2		8640	17280	6DP-STT
4	1		6400	12800	9P-STT
4	2		11520	23040	9DP-STT
6	1		7200	14400	6V-STT
6	2		12240	24480	6DV-STT
6	1		9600	19200	9V-STT
6	2		16320	32640	9DV-STT
8	1		12800	25600	9W-STT
8	2		20480	40960	9DW-STT
10	1		16000	32000	9X-STT
10	2		24000	48000	9DX-STT
12	1		19200	38400	9Y-STT
12	2		26880	53760	9DY-STT

BASKET AND CHOKER STEEL HARDWARE

WSA TYPE II BASKET AND CHOKER SLING TRIANGLE ONE END CHOKER TRIANGLE OTHER END



WIDTH INCHES	NUMBER PLIES	RATED CAPACITY (LBS) SAFETY FACTOR 5 TO 1			CODE NUMBER
		CHOKER	VERTICAL	BASKET	
2	1	1920	2400	4800	6I-STC
2	2	3840	4800	9600	6DI-STC
2	1	2560	3200	6400	9I-STC
2	2	4960	6200	12400	9DI-STC
3	1	2880	3600	7200	6M-STC
3	2	5320	6660	13320	6DM-STC
3	1	3840	4800	9600	9M-STC
3	2	7100	8880	17760	9DM-STC
4	1	3840	4800	9600	6P-STC
4	2	6910	8640	17280	6DP-STC
4	1	5120	6400	12800	9P-STC
4	2	9210	11520	23040	9DP-STC
6	1	5760	7200	14400	6V-STC
6	2	9790	12240	24480	6DV-STC
6	1	7680	9600	19200	9V-STC
6	2	13050	16320	32640	9DV-STC
8	1	10240	12800	25600	9W-STC
8	2	16380	20480	40960	9DW-STC
10	1	12800	16000	32000	9X-STC
10	2	19200	24000	48000	9DX-STC
12	1	15360	19200	38400	9Y-STC
12	2	21500	26880	53760	9DY-STC

