

## Grade 80 Alloy Chain

### SPECTRUM 8® ALLOY CHAIN



- Alloy Steel.
- Heat Treated.
- Finish - Black Thermadep Coating.
- Permanently embossed with CG (Crosby Group) and 8 (Grade).
- Proof Tested to 2 times the Working Load Limit with certification.

**GRADE 80 ALLOY CHAIN** recommended for overhead lifting applications.

Chain Size (in.)	Spec.8 Drum Stock No.	Feet Per Drum	Material Size (in.)	Working Load Limit (lbs.)*	Maximum Inside Length (in.)	Minimum Inside Width (in.)	Maximum Length 100 Links (in.)	Weight Per 100 Ft. (lbs.)
9/32 (1/4)	273527	500	.276	3500	.87	.42	90	72
5/16	273536	500	.343	4500	1.01	.49	100	114
3/8	273545	500	.394	7100	1.23	.58	125	148
1/2	273554	300	.512	12000	1.57	.77	164	243
5/8	273563	200	.630	18100	1.93	.90	202	351
3/4	273572	100	.787	28300	2.42	1.14	252	584
7/8	273581	100	.866	34200	2.66	1.26	277	705

\* Proof Loaded at 2 times the Working Load Limit. Minimum Ultimate Load is 4 times the Working Load Limit.

**Crosby provides two methods of attaching  
Spectrum 8® chain to Crosby fittings**



**A-1337  
Lok-A-Loy®  
Connecting Link**



**S-1325  
Grade 100  
Coupler link**