

Grade 100 Alloy Chain

SPECTRUM 10® ALLOY CHAIN™



- Alloy Steel
- Heat Treated
- 25% stronger than Grade 80 Alloy Chain
- Permanently embossed with CG (Crosby Group) and 10 (Grade).
- Finish - Black Thermadep Coating.
- Proof Tested at 2 times the Working Load Limit with certification.
- Standard container - fiber drum

Grade 100 Alloy Chain recommended for overhead lifting applications"

Chain Size		Gr.100 Drum Stock No.	Feet Per Drum	Size Material (in.)	Working Load Limit (lbs.)*	Maximum Inside Length (in.)	Minimum Inside Width (in.)	Maximum Length 100 Links (in.)	Weight Per 100 Feet (lbs.)
(in.)	(mm)								
9/32 (1/4)	7	273710	500	.276	4300	.87	.42	90	75A
5/16	8	273729	500	.343	5700	1.01	.49	100	113A
3/8	10	273738	500	.394	8800	1.23	.58	125	148A
1/2	13	273747	300	.512	15000	1.57	.77	164	249A
5/8	16	273756	200	.630	22600	1.93	.90	202	378A

* Proof loaded at 2 times Working Load Limit. Minimum Ultimate Load is 4 times the Working Load Limit.




Fatigue Rated Crosby 8/10™

A-1337



- Suitable for use with both Grade 80 and Grade 100 chain.
- Individually Proof Tested at 2-1/2 times Working Load Limit with certification.
- Locking system that provides for simple assembly and disassembly - no special tools needed.
- 25% stronger than Grade 80.
- Meets ASTM A-952-96 standards for Grade 100 chain fittings.
- Forged Alloy Steel - Quenched and Tempered.
- Fatigue rated.



LOK-A-LOY® 10 Alloy Connecting Link

Chain Size		A-1337 Stock No.	Pkg. Qty.	Weight Each (lbs.)	Working Load Limit (lbs.)*	Dimensions (in.)					
(in.)	(mm)					A	B	C	D	E	F
9/32 (1/4)	7	1015104	60	.26	4300	.38	1.94	1.90	.81	.69	.57A
5/16	8	1015113	50	.35	5700	.37	2.35	2.07	.99	.72	.64A
3/8	10	1015122	40	.75	8800	.48	2.70	2.47	1.12	.90	.78A
1/2	13	1015136	12	1.55	15000	.64	3.45	3.23	1.44	1.12	.97A
5/8	16	1015145	10	2.68	22600	.75	4.13	3.78	1.72	1.34	1.14A
3/4	20	1015154	1	5.00	35300	.93	4.62	4.62	2.03	1.62	1.28A
7/8	22	1015163	1	7.50	42700	1.06	5.46	5.46	2.27	2.00	1.49A
1	25	1015172	1	11.03	59700	1.22	5.98	6.13	2.44	2.25	1.76
1-1/4	32	1015181	1	20.38	90400	1.50	7.43	7.59	3.07	2.56	2.23A

* Ultimate Load is 4 times the Working Load Limit.

Copyright © 2008 The Crosby Group, Inc.
All Rights Reserved

