

# Double Braid

## Nylon Double Braid Rope

High strength, high stretch, torque free, excellent shock absorption, good resistance to abrasion, ultraviolet rays and common chemicals. Due to its high elongations, nylon is almost always used in applications involving shock loading such as anchor lines and mooring lines.

Item No.	Diameter	Length	Approx. Tensile	Approx. Wt.
345015	1/4"	600'	2,300 lbs	10 lbs
345025	5/16"	600'	3,400 lbs	16 lbs
345035	3/8"	600'	4,900 lbs	22 lbs
345045	7/16"	600'	6,600 lbs	30 lbs
345050	1/2"	600'	8,500 lbs	40 lbs
345060	5/8"	600'	15,200 lbs	70 lbs
346070	3/4"	600'	19,100 lbs	88 lbs
346107	7/8"	600'	28,300 lbs	130 lbs
346110	1"	600'	33,600 lbs	156 lbs
346125	1-1/8"	600'	45,000 lbs	212 lbs
346127	1-1/4"	600'	52,000 lbs	244 lbs
346130	1-1/2"	600'	74,000 lbs	350 lbs
346135	1-5/8"	600'	91,000 lbs	434 lbs
346137	1-3/4"	600'	110,000 lbs	526 lbs
346140	2"	600'	131,000 lbs	625 lbs

\*Larger sizes are available upon request.



## Polyester Double Braid Rope

High strength, low stretch, torque free, excellent wet/dry abrasion resistance and wet/dry strength. Good resistance to ultraviolet rays and common chemicals, Has the best weathering characteristics of all popular fibers.

Item No.	Diameter	Length	Approx. Tensile	Approx. Wt.
347020	1/4"	600'	2,800 lbs	14 lbs
347030	5/16"	600'	4,200 lbs	22 lbs
347040	3/8"	600'	5,600 lbs	29 lbs
347050	7/16"	600'	7,400 lbs	38 lbs
347060	1/2"	600'	9,900 lbs	52 lbs
347070	9/16"	600'	12,600 lbs	67 lbs
347100	5/8"	600'	15,500 lbs	79 lbs
348110	3/4"	600'	20,000 lbs	113 lbs
348123	7/8"	600'	28,500 lbs	154 lbs
348125	1"	600'	36,300 lbs	201 lbs
348130	1-1/8"	600'	46,000 lbs	254 lbs

\*Larger sizes are available upon request.

