



Super Dyna (100% Super High Strength Polyolefin Yarns) Ship Mooring Lines - "8" Braid Hawsers

Two times the wear life of polypropylene, 20% to 25% stronger than polypropylene, non torque construction, good UV resistance, a abrasion resistance, floats in water, excellent resistance to most common chemicals, rot and mildew

Item No.	Diameter	Length	Size	Min. Tensile	Approx. Wt.
403647	2"	720'	50 mm	64,000 lbs	498 lbs
403652	2-1/4"	720'	56 mm	88,000 lbs	660 lbs
403655	2-1/2"	720'	60 mm	100,000 lbs	770 lbs
403662	2-5/8"	720'	64 mm	115,000 lbs	864 lbs
403665	3"	720'	72 mm	146,000 lbs	1102 lbs
403670	3-1/4"	720'	80 mm	175,000 lbs	1398 lbs
403675	4"	720'	96 mm	240,000 lbs	1960 lbs

"8" Braid SUPER BLUE STEEL™ Poly

High strength coextrusion polyolefin yarns, 35% to 40% stronger than polypropylene, non torque construction, superior UV resistance over polypropylene, Superior abrasion resistance, floats in water, excellent resistance to most common chemicals, rot and mildew.

Item No.	Coil/ Reel	Diameter	Length	Average Tensile	Approx. Wt.
402118	Coil	1"	600'	26,400 lbs	115 lbs
402123	Coil	1-1/8"	600'	35,100 lbs	158 lbs
402130	Coil	1-1/4"	600'	38,100 lbs	178 lbs
402137	Coil	1-1/2"	600'	55,800 lbs	318 lbs
402143	Reel	1-5/8"	600'	68,700 lbs	336 lbs
402146	Coil	1-3/4"	600'	74,700 lbs	393 lbs
402147	Reel	1-3/4"	600'	74,700 lbs	393 lbs
402155	Coil	2"	600'	91,400 lbs	481 lbs
402156	Reel	2"	600'	91,400 lbs	481 lbs
402165	Coil	2-1/4"	600'	120,600 lbs	651 lbs
402166	Reel	2-1/4"	600'	120,600 lbs	651 lbs
402180	Coil	2-1/2"	600'	137,800 lbs	747 lbs
402181	Reel	2-1/2"	600'	137,800 lbs	747 lbs
402188	Coil	2-5/8"	600'	155,000 lbs	846 lbs
402200	Coil	3"	600'	197,100 lbs	1068 lbs
402210	Coil	3-1/4"	600'	238,800 lbs	1320 lbs
402225	Coil	4"	600'	338,800 lbs	1887 lbs

Nylon "8" Braid

High elongation and strength, good energy absorption, non torque construction good abrasion resistance, superior UV resistance, rot, mildew, oil, grease, gasoline and most common chemicals.

Item No.	Diameter	Length	Average Tensile	Approx. Wt.
409126	2"	600'	96,900 lbs	636 lbs
409131	2 5/8"	600'	163,800 lbs	1086 lbs
409136	3"	600'	209,800 lbs	1422 lbs
409138	3-1/4"	600'	248,800 lbs	1728 lbs
409145	4"	600'	356,400 lbs	2520 lbs