

Braided - 12 Strand

BLUE STEEL™ Copolymer 12 Strand

High strength coextrusion polyolefin yarns, 35% to 40% stronger than polypropylene, flexible non rotating construction, superior UV resistance over polypropylene, Superior abrasion resistance, floats in water, excellent resistance to most common chemicals, rot and mildew, easily spliced.

Item No.	Diameter	Length	Minimum Tensile	Approx. Wt./100
353310	1/2"	600'	6,900 lbs	5.4 lbs
353320	5/8"	600'	12,000 lbs	9.6 lbs
353325	3/4"	600'	15,900 lbs	12.5 lbs
353328	7/8"	600'	21,200 lbs	17 lbs
353330	1"	600'	25,000 lbs	19.4 lbs
353334	1-1/8"	600'	33,500 lbs	26.5 lbs

*Sizes 1-1/4" through 2" also available by special order only.



Spectra® 12 Strand

Very high strength synthetic rope with excellent abrasion resistance in a single braid construction. It comes standard with a polyurethane finish and is easily spliced using a lockstitch type splice, 4-3-2 or 5-4-3 Tuck splice. It also has a low stretch, low creep, soft hand, is torque-free and it floats.

Diameter	Minimum Tensile	Approx. Wt./100
1/2"	22,500 lbs	6.4 lbs
5/8"	36,600 lbs	10.6 lbs
3/4"	43,200 lbs	13.3 lbs
1"	72,000 lbs	23.4 lbs
1-1/2"	141,300 lbs	51.7 lbs
2"	225,000 lbs	91.4 lbs
2-1/2"	360,000 lbs	148 lbs

All other sizes are available.



Plasma® 12 Strand

Highest strength synthetic rope available. It comes standard with a polyurethane finish and is easily spliced using a lockstitch type splice, 4-3-2 or 5-4-3 Tuck splice. It also has the lowest stretch, low creep, soft hand, is torque-free and it floats.

Diameter	Minimum Tensile	Approx. Wt./100
1/2"	31,300 lbs	6.4 lbs
5/8"	51,400 lbs	10.6 lbs
3/4"	68,500 lbs	13.3 lbs
1"	110,000 lbs	23.4 lbs
1-1/2"	221,000 lbs	51.7 lbs
2"	355,000 lbs	91.4 lbs
2-1/2"	530,000 lbs	148 lbs

All other sizes are available.

