

EQUIPMENT FOR SELF-PROPELLED OCEAN-GOING STEEL VESSELS

Equipment Numeral	Equipment Number*	Stockless Bow Anchor			Chain Cable Stud Link Bower Chain		
		Number	Mass per Anchor, pounds	Length, fathoms	Diameter		
					Normal-Strength Steel (Grade 1), inches	High-Strength Steel (Grade 2), inches	Extra High-Strength Steel (Grade 3), inches
U6	150	3	1060	150	7/8	3/4	
U7	175	3	1255	165	15/16	13/16	
U8	205	3	1455	165	1	7/8	13/16
U9	240	3	1720	180	1-1/8	15/16	7/8
U10	280	3	1985	195	1-3/16	1	15/16
U11	320	3	2250	195	1-1/4	1-1/8	15/16
U12	360	3	2510	210	1-5/16	1-3/16	1
U13	400	3	2840	210	1-7/16	1-1/4	1-1/8
U14	450	3	3170	225	1-1/2	1-5/16	1-3/16
U15	500	3	3500	225	1-9/16	1-5/16	1-3/16
U16	550	3	3830	240	1-5/8	1-7/16	1-1/4
U17	600	3	4230	240	1-3/4	1-1/2	1-5/16
U18	660	3	4630	240	1-13/16	1-9/16	1-7/16
U19	720	3	5020	255	1-7/8	1-5/8	1-7/16
U20	780	3	5420	255	2	1-3/4	1-1/2
U21	840	3	5820	255	2-1/16	1-13/16	1-9/16
U22	910	3	6280	270	2-1/8	1-7/8	1-5/8
U23	980	3	6740	270	2-3/16	1-15/16	1-3/4
U24	1060	3	7270	270	2-5/16	2	1-13/16
U25	1140	3	7800	285	2-3/8	2-1/16	1-13/16
U26	1220	3	8330	285	2-7/16	2-1/8	1-7/8
U27	1300	3	8930	285	2-1/2	2-3/16	2
U28	1390	3	9520	300	2-5/8	2-5/16	2
U29	1480	3	10120	300	2-11/16	2-3/8	2-1/16
U30	1570	3	10800	300	2-3/4	2-7/16	2-1/8
U31	1670	3	11600	315	2-7/8	2-1/2	2-3/16
U32	1790	3	12400	315	3	2-5/8	2-5/16
U33	1930	3	13200	315	3-1/16	2-11/16	2-3/8
U34	2080	3	14200	330	3-3/16	2-3/4	2-7/16
U35	2230	3	15200	330	3-5/16	2-7/8	2-1/2
U36	2380	3	16200	330	3-7/16	3	2-5/8
U37	2530	3	17200	345	3-9/16	3-1/16	2-11/16
U38	2700	3	18300	345	3-5/8	3-3/16	2-3/4
U39	2870	3	19200	345	3-3/4	3-5/16	2-7/8
U40	3040	3	20500	360	3-7/8	3-5/16	3

EQUIPMENT FOR SELF-PROPELLED OCEAN-GOING STEEL VESSELS

Equipment Numeral	Equipment Number*	Stockless Bow Anchor		Chain Cable Stud Link Bower Chain			
		Number	Mass per Anchor, pounds	Length, fathoms	Diameter		
					Normal-Strength Steel (Grade 1), inches	High-Strength Steel (Grade 2), inches	Extra High-Strength Steel (Grade 3), inches
U41	3210	3	21800	360	3-15/16	3-7/16	3-1/16
U42	3400	3	23100	360	4	3-9/16	3-1/16
U43	3600	3	24500	375	4-1/8	3-5/8	3-3/16
U44	3800	3	25800	375	4-1/4	3-3/4	3-5/16
U45	4000	3	27100	375	4-3/8	3-7/8	3-7/16
U46	4200	3	28400	390	4-1/2	3-15/16	3-7/16
U47	4400	3	29800	390	4-5/8	4	3-9/16
U48	4600	3	31100	390	4-3/4	4-1/8	3-5/8
U49	4800	3	32400	405	4-3/4	4-1/4	3-3/4
U50	5000	3	33900	405	4-7/8	4-3/8	3-7/8
U51	5200	3	35500	405	5	4-3/8	3-7/8
U52	5500	3	37200	405	5-1/8	4-1/2	3-15/16
U53	5800	3	39200	405	5-1/8	4-5/8	4
U54	6100	3	41400	405		4-3/4	4-1/4
U55	6500	3	44000	420		4-7/8	4-3/8
U56	6900	3	47400	420		5	4-1/2
U57	7400	3	50700	420		5-1/8	4-5/8
U58	7900	3	54000	420		5-3/8	4-3/4
U59	8400	3	57300	420		5-5/8	5
U60	8900	3	60600	420		5-3/4	5-1/8
U61	9400	3	63900	420		6	5-1/8
U62	10000	3	68000	420			5-3/8
U63	10700	3	72500	420			5-5/8
U64	11500	3	78000	420			5-3/4
U65	12400	3	85000	420			6
U66	13400	3	92500	420			6-1/8
U67	14600	3	101500	420			6-3/8

* For intermediate values of equipment number use equipment complement in sizes and weights given for the lower equipment number in the table.

American Bureau of Shipping (1998), Rules for Building and Classing Steel Vessels 1998-1999, Part 3 Hull Construction and Equipment, pp. 140-141.

The requirements as contained in this table are subject to change.

