



**LARGER SIZES
AVAILABLE AS
REQUIRED.**

DCL ROV Hooks are designed for ease, reliability, and safe operation in installation and retrieval of subsea equipment. The entire ROV Friendly mechanism is manufactured from stainless steel. Hooks are constructed from alloy steel. ROV Hooks can be proof tested and load certified to 2 1/2 times the Working Load Limit (WLL).

| Tons | C | D | F | G | J | K | M | N | O | O2 | Q | T | T2 | AA |
|------|-------|-------|------|------|------|------|------|------|------|------|------|------|------|-------|
| 5 | 5.77 | 4.81 | 2.00 | 1.44 | 1.47 | 1.31 | 1.31 | 0.72 | 1.36 | 1.00 | 1.56 | 1.53 | 1.50 | 2.50 |
| 7 | 7.37 | 6.27 | 2.50 | 1.81 | 1.75 | 1.66 | 1.66 | 0.90 | 1.61 | 1.31 | 2.00 | 1.96 | 1.88 | 3.00 |
| 11 | 9.07 | 7.45 | 3.00 | 2.25 | 2.29 | 1.88 | 1.63 | 1.11 | 2.08 | 1.18 | 2.44 | 2.47 | 2.25 | 4.00 |
| 15 | 10.08 | 8.30 | 3.25 | 2.59 | 2.50 | 2.19 | 1.94 | 1.27 | 2.27 | 2.00 | 2.84 | 2.62 | 2.31 | 4.00 |
| 22 | 12.53 | 10.30 | 4.25 | 3.00 | 3.30 | 2.69 | 2.38 | 1.56 | 3.02 | 2.75 | 3.50 | 2.83 | 2.56 | 5.00 |
| 30 | 14.06 | 13.62 | 5.00 | 3.62 | 4.00 | 3.00 | 3.00 | 1.75 | 3.25 | 0.00 | 3.50 | 3.44 | 0.00 | 6.50 |
| 37 | 18.19 | 14.06 | 5.38 | 4.56 | 4.25 | 4.00 | 3.19 | 2.00 | 3.00 | 0.00 | 4.50 | 3.88 | 0.00 | 7.00 |
| 45 | 20.12 | 15.44 | 6.00 | 5.06 | 4.75 | 4.50 | 3.25 | 2.18 | 3.38 | 0.00 | 4.94 | 4.75 | 0.00 | 8.00 |
| 60 | 23.72 | 18.50 | 7.00 | 6.00 | 5.75 | 5.50 | 3.91 | 2.53 | 4.12 | 0.00 | 5.69 | 5.69 | 0.00 | 10.00 |