## THIMBLE Rope Thimbles



**ROPE THIMBLE** LB303

LBNO new dimension "LIGHTER WEIGHT" heavy duty Rope Thimble is an improved design for the marine towing industry use. Light enough for ease of handling, but with maximum high strength at critical points. The generous inside dimensions allow for these thimbles to fit our LBNO Marine Towing Shackles, or any large regular shackle.

When ordering Always Specify **LBNO Quality Rope Thimbles**. All of these advantages have been demonstrated over and over again, by outstanding on-the-job performance.

ROPE THIMB	HIGH STRENGTH STEEL – SELF-COLORED & GALVANIZED –							
Rope	Rope Circum-	DIMENSION IN INCHES						Weight
Diameter Inches	ferences Inches	Α	В	С	D	E	w	Pounds Each
<b>1 - 1</b> <sup>1</sup> / <sub>4</sub>	3 - 33/4	2	<b>3</b> <sup>1</sup> / <sub>2</sub>	5 <sup>3</sup> / <sub>8</sub>	1º/ <sub>16</sub>	<b>1</b> <sup>7</sup> / <sub>16</sub>	115/16	2 <sup>1</sup> / <sub>2</sub>
1 <sup>5</sup> / <sub>16</sub> -1 <sup>5</sup> / <sub>8</sub>	4 & 5	33/8	5 <sup>1</sup> / <sub>8</sub>	<b>7</b> 7/ <sub>8</sub>	1 <sup>13</sup> / <sub>16</sub>	<b>1</b> 3/4	2 <sup>1</sup> / <sub>4</sub>	$5^{1/2}$
2 & 2 <sup>1</sup> / <sub>4</sub>	6 & 7	3 <sup>1</sup> / <sub>8</sub>	6	9 <sup>1</sup> / <sub>4</sub>	2 <sup>3</sup> /4	2 <sup>3</sup> / <sub>4</sub>	3 <sup>3</sup> /8	11
2 <sup>5</sup> / <sub>8</sub>	8	4 <sup>1</sup> / <sub>4</sub>	6 <sup>1</sup> / <sub>2</sub>	11	3 <sup>1</sup> / <sub>8</sub>	3	<b>3</b> <sup>3</sup> / <sub>4</sub>	20 <sup>1</sup> / <sub>2</sub>
3	9	4 <sup>3</sup> / <sub>4</sub>	7 <sup>5</sup> /8	12	3 <sup>1</sup> / <sub>2</sub>	31/4	4	26
31/4	10	5	<b>8</b> <sup>1</sup> / <sub>2</sub>	13 <sup>1</sup> / <sub>2</sub>	37/8	31/2	41/4	351/2
3 <sup>5</sup> / <sub>8</sub> - 4	11 - 12	6 <sup>1</sup> / <sub>8</sub>	9 <sup>1</sup> / <sub>2</sub>	15 <sup>1</sup> / <sub>2</sub>	5 <sup>3</sup> /8	4 <sup>1</sup> / <sub>2</sub>	5 <sup>1</sup> / <sub>2</sub>	48
4 <sup>1</sup> / <sub>4</sub> - 4 <sup>5</sup> / <sub>8</sub>	13 - 14	6	10	17	5 <sup>3</sup> /4	5 <sup>1</sup> / <sub>4</sub>	6	56 <sup>1</sup> / <sub>2</sub>
5 - 5 <sup>1</sup> / <sub>4</sub>	15 - 16	<b>6</b> <sup>7</sup> / <sub>16</sub>	11	18 <sup>1</sup> / <sub>2</sub>	6 <sup>1</sup> / <sub>2</sub>	5 <sup>3</sup> /4	6 <sup>5</sup> / <sub>8</sub>	64
5 <sup>5</sup> / <sub>8</sub> - 6	17 - 18	10	117/8	24	6 <sup>1</sup> / <sub>2</sub>	6 <sup>1</sup> / <sub>8</sub>	7	80
61/4 - 65/8	19 - 20	12	16 <sup>1</sup> /4	27	8	73/4	9	270
7 - 71/4	21 - 22	13 <sup>7</sup> /8	193/4	333/4	9 <sup>1</sup> / <sub>4</sub>	<b>8</b> <sup>1</sup> / <sub>2</sub>	101/4	378

\*NOTE: Can be made of Stainless Steel.

\*NOTE: Dimensions are approximate in accordance with Standard Foundry Practice.

\*NOTE: "D" Dimension is larger than "E" Dimension to allow for the larger diameter of the rope after splicing.



(в7)